

Specs for in-field groomer

Engine:

- Minimum 16 horse power, air cooled V-twin

Transmission:

- Infinitely Variable 0 – 10 mph forward
- Infinitely Variable 0 – 4 mph reverse

Instruments & Gauges:

- Hour meter
- Hand operated choke throttle
- Rear hydraulic controls (Raise, lift, lower and float position)
- Single foot pedal control for forward and reverse

Chassis:

- Series/Parallel™ 3 wheel hydrostatic drive unit
- Minimum 6" ground clearance with mid-mount tool bar
- Minimum 8" turning radius
- Environmentally sealed gear drive steering
- Flip up seat for easy access to scheduled maintenance
- Trash/Rock container, Radio holder, and drink holder

Hydraulics:

- Rear remote hydraulics to power attachments
- Visual and physical differences between gas and hydraulic tank caps

Attachments:

- Quick Attach System (Change attachment in under a minute)
- Front, Mid-mount and Rear attachments
- Flex mounted Mid-mount toolbar to reduce operator influence and reduce damage to the machine (Solid, Carbide, Spring, and Weeder Tine options)
- Spring Balanced Manual Blade with quick latch mechanism for transport

- 16+ attachments available to increase versatility and productivity

Warranty:

- 2 year or 1500 hour factory warranty